



Presentation image. Final colour may vary.

Ref. HE-D103

3,800 A steel spotter with dual display

3,800 A steel spotter: tool and power shown on two displays, manual or automatic spotting.

Steel spotter for all panel pulling and straightening work. The microprocessor reduces setup to choosing the tool (7 tools) and the power level (11 levels), both shown on two displays. The weld fires from the trigger or automatically on contact with the panel. Supplied with a slide hammer for the gun, a hook hammer and a full kit of pulling consumables.

Technical specifications

Supply voltage	220 V or 380 V – 50/60 Hz
Continuous power	3 kW
Max. welding current	3,800 A
Panel thickness	0.4 to 1.2 mm
Settings	7 tools × 11 power levels
Open-circuit voltage	7.2 V
Firing mode	Manual / automatic
Machine package weight	27 kg
Display	Digital, 2 displays
Panels worked	Steel
Format	Portable, trolley optional

Key features

- Max. welding current 3,800 A
- Dual tool / power display
- 7 tools × 11 power levels
- Manual or automatic firing
- 7 programmes, including single-sided spot welding and heat shrinking
- Oxygen-free pure copper cable

How to use

- Dent repair on steel panels (bonnet, door, roof, wing)
- Spotter pulling with stars, washers and rings
- Wiggle wire welding on curved profiles (wheel arch)
- Panel shrinking with the carbon electrode
- Stud welding
- Single-sided spot welding

Packaging and delivery

Version	Reference
Front panel without cover	HE-D103-A
Front panel with clear protective cover	HE-D103-B

What's in the box

- Copper-plated pulling stars ×10
- Pulling washers ×20
- Slide hammer for gun ×1
- Hook slide hammer ×1
- OT pulling rings ×10
- Carbon electrode holder ×1
- Spanner ×1
- Suction cup ×1
- Wiggle wires ×10
- Washer / OT ring tip ×1
- Dual-purpose spot welding tip ×1
- Carbon electrodes ×2
- 6-hook pulling claw ×1
- Accessory case ×1

This product is available from Humming distributors. Find the one nearest to you.