



Presentation image. Final colour may vary.

Ref. HE-L502

2-cassette short-wave infrared curing lamp

Two IR cassettes, 2,400 W in total, for curing 800 × 800 mm with time and temperature control.

Two-cassette short-wave infrared curing lamp on a mobile stand, for medium-sized repairs. Short waves penetrate the product layer and cure it through and on the surface at the same time: around 15 minutes instead of 45 with long-wave infrared. Suitable for steel and aluminium. The analogue control version sets time, temperature and height, and switches each cassette on separately. The digital version adds pulse curing and motorised raising / lowering at the touch of a button. Three arm mountings let you reach the roof or work around the vehicle.

Technical specifications

Supply voltage	220 V
Frequency	50/60 Hz
Maximum power	2,400 W
Current draw	10 to 11 A
Curing area	800 × 800 mm
Number of cassettes	2
Display	Analogue or digital depending on model
Mobility	Mobile stand
Settings (analogue version)	Timer graduated from 10 to 60 with off / on positions, thermostat graduated from 40 to 100, switch for each cassette (A / B)
Settings (digital version)	Time and power displays with +/– buttons, cassette selection, pulse / continuous mode, on / off

Key features

- Adjustable temperature and time
- Adjustable height
- Cassette-by-cassette control
- Digital version: pulse curing and motorised lifting
- Horizontal arm for the roof, 360° swivel head or ram-assisted arm depending on model

How to use

- Curing filler, primer, paint and clear coat
- Medium-sized body panels
- Roof (arm version)

Packaging and delivery

Version	Reference	
Digital version with motorised lifting	HE-L502-A	Pulse curing, one-touch lifting; package 1: 73 × 23 × 78 cm, 14 kg; package 2: 6 × 6 × 152 cm, 1.5 kg
Analogue version with horizontal arm	HE-L502-B	For curing the roof; package 1: 73 × 23 × 78 cm, 16 kg; package 2: 6 × 6 × 152 cm, 2 kg
Analogue version, 360° swivel	HE-L502-C	360° rotating head; package 1: 73 × 23 × 78 cm, 14 kg; package 2: 6 × 6 × 152 cm, 1.5 kg
Analogue version with ram-assisted arm	HE-L502-D	Hydraulic ram-assisted arm, any height; package 1: 73 × 23 × 78 cm, 8 kg; package 2: 154 × 17 × 65 cm, 31 kg

Package dimensions : Depends on version, see variants · Package weight : Depends on version, see variants

This product is available from Humming distributors. Find the one nearest to you.