



Presentation image. Final colour may vary.

Ref. HE-P301

1,600 W mobile extraction unit – 50 L tank

50 L dust-free sanding unit on a trolley: over 95 % of dust captured at source.

Mobile extraction unit for dust-free sanding, with a 50 L tank, push handle and hose holder. It supplies air to pneumatic sanders and also works with electric sanders. The copper-wound motor, cooled by dual airflow, runs through long sessions without overheating, and the turbine keeps noise down. 5-layer filtration returns clean air to the workshop; the tank opens easily for emptying and the suction power can be adjusted to suit the job. Four configurations available, with or without a tool column and front control panel.

Technical specifications

Supply voltage	220 V
Frequency	50/60 Hz
Rated power	1,600 W
Required air flow	≥ 300 L/min
Air pressure	8 bar
Tank capacity	50 L
Format	Trolley-mounted

Key features

- Dust capture above 95 %
- Copper-wound motor cooled by dual airflow
- Low-noise turbine
- 5-layer filtration, clean exhaust air
- Easy-open tank for emptying
- Adjustable suction power
- Pneumatic or electric sanders (optional kits)

How to use

- Dust-free sanding of filler and primer
- Substrate preparation before painting
- Sanding with extraction hand blocks and orbital sanders

Packaging and delivery

Version	Reference
Standard trolley	HE-P301-A Handle and hose holder; package 63 × 47 × 65 cm, 32.5 kg
Trolley with tool column	HE-P301-B Column with sander holder, disc holder and shelf; package 63 × 47 × 65 cm, 35.5 kg

Version	Reference	
Standard trolley, front control panel	HE-P301-C	Front display and switches; package 63 × 47 × 65 cm, 32.5 kg
Trolley with tool column, front control panel	HE-P301-D	Column with sander holder, disc holder and shelves; package 63 × 47 × 65 cm, 35.5 kg

Package dimensions : 63 × 47 × 65 cm · Package weight : 32.5 kg (standard trolley) / 35.5 kg (with column)

This product is available from Humming distributors. Find the one nearest to you.